

## ADA CHECKLIST DOCUMENT 2 FOR TRAFFIC CONTROL SIGNALS

Last Update: 12/24/2014

	Intersection Name:	Date:	References: PROWAG July 26, 2011 and 2009 MUTCD
	Municipality:		
	Traffic Control Signal Location:		
	Traffic Control Signal questions		
1	Is an accessible pedestrian pushbutton signal provided for each crosswalk?	Y / N	R209.1
2	Is the pedestrian pushbutton unobstructed and adjacent to a level all-weather surface providing wheelchair access with the required clear space?	Y / N	R403, R404, MUTCD 4E.08
3	Is the unobstructed horizontal side reach to the pushbutton 10" or less?	Y / N / NA Inch (If no or N/A then go to #4)	R406.3
4	Is the unobstructed horizontal forward reach to the pushbutton 0"?	Y / N / NA (If no or N/A then #3 applies)	R406.2
5	Is the pedestrian pushbutton located between edge of crosswalk line and side of curb ramp, but not more than 5' from crosswalk line extended?	Y / N Ft	R209.1, MUTCD 4E.08, MUTCD 4E.10
6	Is the pedestrian pushbutton located between 1.5' (18") and 6' from edge of curb, shoulder or pavement?	Y / N Ft/Inch	R209.1, MUTCD 4E.08
7	Is the face of the pushbutton parallel to the direction of the corresponding crosswalk to be used?	Y / N	R209.1, MUTCD 4E.08
8	Is the pushbutton mounted between 3.5' (42") and not more than 4' (48") above the sidewalk?	Y / N Ft/Inch	R209.1, R406.2, MUTCD 4E.08
9	If there are two pushbuttons provided on the same corner of a signalized intersection, are they located at least 10' apart (where practicable)?	Y / N (If no skip to #11)	R209.1, MUTCD 4E.08
10	If two pushbuttons on the same corner are located at least 10' apart, do they provide a speech walk message?	Y / N / NA	R209.1, R406.2, MUTCD 4E.11
11	If two pushbuttons on the same corner must be located less than 10' apart or on same pole, do they provide a pushbutton locator tone, vibro-tactile arrow, audible speech walk message and speech pushbutton information message?	Y / N / NA	R209.1, MUTCD 4E.10-13
12	Is the street name also encoded into Braille on the pedestrian instruction sign (either Type R10-3 or Type R10-4)?	Y / N	28 CFR 35.160, MUTCD 4E09.11
13	Are vibro-tactile arrows located on the pushbutton or another part of the APS device, have high visual contrast and aligned parallel to direction of travel on associated crosswalk?	Y / N / NA	R209.1, MUTCD 4E.12
14	Do any mounted signs or objects with bottom edge between 2.25' (27") and 6.7' (80") above finished surface protrude only 4" or less into pedestrian access route?	Y / N / NA Inch	R402.2, R402.3
15	Is the base of the post at least 2.5" thick (is top of base at least 2.5" above finished surface)?	Y / N Inch	R402.3

**Any "N" response indicates a non ADA compliant Traffic Control Signal. However, all "Y" responses do not necessarily indicate an ADA compliant Traffic Control Signal. This check list is only an aid for identifying non ADA compliant Traffic Control Signals. It is not a substitute for the ADA requirements. See the Access Board's GUIDANCE ISSUED ON DIMENSIONAL TOLERANCES FOR ACCESSIBLE SURFACES, February 23, 2011, specifically the report "Dimensional Tolerances for Surface Accessibility" which provides measurement conventions, tolerances and construction variation.**